

Solid-Inker Printing Sealer
With Stand Model



Model	SF150G
Power supply	110V,220-240V/50-60Hz 1Phase
Power consumption	750W
Sealing speed	0-13m/min
Sealing width	6-15mm
Sealing film thickness	0.02-0.08mm
Temperature range	0-300jæ
Printing letters	1 lines 15 letters
Conveyor loading	5kg
Machine size	930jÁ510jÁ920mm
Machine weight	65kg

Multi-Functional Film Sealer
Vertical Model SF150LW



Model	SF-150LW	SF-150LD
Power supply	110V,220-240V/50-60Hz	1Phase
Power consumption	500W	500W
Sealing speed	0-12m/min	0-12m/min
Sealing width	6-15mm	6-15mm
Sealing film thickness	0.02-0.08mm	0.02-0.08mm
Temperature range	0-300iæ	0-300iæ
Printing letters	1 lines 15 letters (steel pressing wheel printing)	
Conveyor loading	5Kg	5Kg
Machine size	900iÁ420iÁ660mm	900iÁ420iÁ1150mm
Machine weight	42kg	45kg

**Multi-Functional Film Sealer
Horizontal Model SF150W**



This series sealer is suitable for small bags packing and adopts electronic constant temperature control system and speed adjusting transmission mechanism. It can seal plastic films of various materials. Such as PE, PP, Aluminum foil. And can be fixed date embossing system. And the newly type (microcomputer control) with counting device (FRD1000)

Model	SF-150W
Power supply	110V,220-240V/50-60Hz 1Phase
Power consumption	500W
Sealing speed	0-12m/min
Sealing width	6-15mm
Sealing film thickness	0.02-0.08mm
Conveyor loading	5kg
Machine size	900iÁ480iÁ380mm
Machine weight	35kg

Solid-Inker Printing Sealer
Vertical Model FRD1000LW



Model	FRD-1000LW	FRD-1000LD
Power supply	110V,220-240V/50-60Hz	1Phase
Power consumption	600W	600W
Sealing speed	0-13m/min	0-13m/min
Sealing width	6-15mm	6-15mm
Sealing film thickness	0.02-0.08mm	0.02-0.08mm
Temperature range	0-300iæ	0-300iæ
Printing letters	2 lines 30 letters with inker	
Conveyor loading	5Kg	5Kg
Machine size	950iÁ400iÁ660mm	950iÁ480iÁ1150mm
Machine weight	46kg	50kg

**Solid-Inker Printing Sealer
Horizontal Model FRD-1000W**



FEATURES

FRD series multi-functional film sealer(with solid inker printer) can be print the desired date date simult -aneously with sealing. With the characters clear and conspicuous , the colors are selectable and uneasy to erase and unchangeable, and instant printing and instant dry. It is convenient t o change date letters.

Power supply	FRD-1000W
Power consumption	110V,220-240V/50-60Hz 1Phase
Sealing speed	600W
Sealing width	0-13m/min
Sealing film thickness	6-15mm
Temperature range	0.02-0.08mm
Printing letters	0-300iæ
Conveyor loading	2 lines 30 letters with inker
Machine size	5kg
Machine weight	950iÁ400iÁ660mm
	45kg

Solid-Inker Printing Sealer
Heavy Duty Model FRL360/600



Model	FRD-1000W
Power supply	110V,220-240V/50-60Hz
Power consumption	830W
Sealing speed	0-13m/min
Sealing width	6-13mm
Sealing film thickness	0.04-0.50mm
Machine size	1200iÁ520iÁ1280mm
Machine weight	98kg